

# Cisco Wireless Phone 800 Series

---

# Contents

Product overview	3
Features and benefits	4
Licensing	4
Product specifications	4
Ordering information	13
Warranty information	16
Cisco environmental sustainability	16
Cisco Capital	16
Document history	17



Cisco Wireless Phones 840 and 860 deliver enterprise-grade voice over IP via wireless smartphones to enable mobility-based productivity.

## Product overview

The Cisco Wireless Phone 800 Series delivers enterprise-grade voice over IP via wireless, handheld devices. The Cisco Wireless Phones provide an application platform that enables third-party applications in a variety of enterprise environments, including healthcare, retail, and manufacturing. These environments require a device that can withstand abuse, while simultaneously enabling users to access information and collaborate quickly and securely with other team members. Cisco Wireless Phones deliver security with AES encryption that ensures secure voice-over-Wi-Fi functionality.

The 800 series phones are built to leverage either Cisco Unified Communications Manager or Webex Calling for call control. Users can take advantage of common enterprise voice features like conference, transfer, and call park. Administrators will relish the ability to manage productivity-enhancing applications through Cisco Meraki System Manager Enterprise Mobility Management (EMM) or alternately through other third-party EMM providers. Users will achieve new levels of success through collaboration applications like Cisco Webex Teams, which is included in the phones.

The 800 series phones are certified for Google Mobility Services and have undergone stringent testing to ensure application compatibility for Android. Like other smart phone hardware and operating systems in the market, third party application compatibility and support is the responsibility of third party application providers.

## Features and benefits

Table 1 outlines some of the key features and benefits of the Cisco Wireless 800 Series Phones.

**Table 1.** Features and benefits

Feature	Benefit
<b>Android Operating System</b>	Enables administrators to control and manage applications deployed to the phones to enable employee productivity
<b>MIL SPEC 810G</b>	Withstands drops to deliver peace of mind and investment protection
<b>IP68 rated hardware (860)</b>	Provides ruggedized hardware that withstands dust and water damage in harsh environments
<b>Hot-swappable battery (860)</b>	Facilitates users to swap batteries in the field without a device restart, providing 100% device uptime
<b>Barcode scanner (optional)</b>	Supports various retail, healthcare, and manufacturing use cases that require barcode scanning

## Licensing

The Cisco Wireless Phone 840 and 860 require an Enhanced User Connect License (UCL) or a Cisco Unified Workspace License (UWL) in order to register to Cisco Unified Communications Manager.

## Product specifications

Table 2 shows the detailed hardware features of the Cisco Wireless Phone 860 and 860S.

**Table 2.** Hardware features

Hardware feature	Cisco Wireless Phone 860 (CP-860)
<b>Weight</b>	204g, 214g (scanner)
<b>Dimensions</b>	153 x 76 x 12 mm
<b>Battery</b>	<ul style="list-style-type: none"><li>• Hot-swappable, 3000 mAh</li><li>• Battery life: Up to 12 hours in call, up to 120 hours idle</li><li>• Charging times when connected to wall power: 3.5 hours for the phone with battery, 3.5 hours for the standalone battery (charging times may vary based on overall battery health and the number of full discharge cycles)</li></ul>

Hardware feature	Cisco Wireless Phone 860 (CP-860)
<b>Input power</b>	100 to 240 VAC, ~0.5A, and 50 to 60 Hz AC adapters (by geographical region)
<b>Processor</b>	1.8/2.2 GHz Octa-core, 64-bit processor
<b>Camera</b>	13 MP rear with flash, 8 MP front
<b>Memory</b>	4 GB
<b>Storage</b>	64 GB
<b>Antenna Type</b>	Dipole (On-Board)
<b>Antenna Gain</b>	<ul style="list-style-type: none"> <li>• 2.4G: 0.6 dBi</li> <li>• 5G: 0.8 dBi</li> </ul>
<b>Frequency Band (MHz)</b>	<ul style="list-style-type: none"> <li>• 2.4G: 2412.0 - 2472.0</li> <li>• 5G: 5150.0 - 5250.0, 5250.0 - 5350.0, 5470.0 - 5725.0, 5745.0 - 5825.0</li> </ul>
<b>Radio frequency standards</b>	2.4 and 5 GHz; 802.11 a/b/g/n/d/h/i/k/r/u/ac
<b>Bluetooth</b>	5.0 LE
<b>Display</b>	5.2-inch 1080x1920, Gorilla™ glass multi-touch screen
<b>Buttons</b>	Power, Action, volume up/down, 2 user-programmable
<b>Operating temperature</b>	32 to 104° F (0 to 40° C)
<b>Storage temperature</b>	-22 to 140° F (-30 to 60° C)
<b>Relative humidity</b>	10% to 95% (noncondensing)
<b>Interfaces</b>	USB-C, 3.5 mm audio, NFC (ISO 14443, Tag Types 1-5), fingerprint scanner
<b>Sensors</b>	<ul style="list-style-type: none"> <li>• Accelerometer</li> <li>• Gyroscope</li> <li>• Magnetometer (compass)</li> <li>• ALS/proximity</li> </ul>
<b>Durability</b>	Ingress Protection Standard IP68 – protects against dust ingress Waterproof – survives water submersion of more than 1 meter for 30+ minutes MIL-STD-810G drop testing – survives 78 1.8 meter drops onto a steel plate

Table 3 shows the detailed hardware features of the Cisco Wireless Phone 840 and 840S.

**Table 3.** Hardware features

Hardware Feature	Cisco Wireless Phone 840 (CP-840)
<b>Weight</b>	180g, 200g (scanner)
<b>Dimensions</b>	133 x 66 x 13 mm
<b>Battery</b>	<ul style="list-style-type: none"> <li>• Swappable, 3040 mAh</li> <li>• Battery life: Up to 17 hours in call, up to 168 hours idles</li> <li>• Charging times when connected to wall power: 3.5 hours for the phone with battery, 3.5 hours for the standalone battery (charging times may vary based on overall battery health and the number of full discharge cycles)</li> </ul>
<b>Input power</b>	100 to 240 VAC, ~0.5A, and 50 to 60 Hz AC adapters (by geographical region)
<b>Processor</b>	1.8 GHz Octa-core, 64-bit processor
<b>Camera</b>	8 MP rear with flash, 2 MP front
<b>Memory</b>	3 GB
<b>Storage</b>	32 GB
<b>Antenna Type</b>	Dipole (On-Board)
<b>Antenna Gain</b>	2.4G: 1.7 dBi 5G: 1.8 dBi
<b>Frequency Band (MHz)</b>	2.4G: 2412.0 - 2472.0 5G: 5150.0 - 5250.0, 5250.0 - 5350.0, 5470.0 - 5725.0, 5745.0 - 5825.0
<b>Radio frequency standards</b>	2.4 and 5 GHz; 802.11 a/b/g/n/d/h/i/k/r/u/ac
<b>Bluetooth</b>	4.2
<b>Display</b>	4.0-inch 800x480, Dragontrail™ glass multi-touch screen
<b>Buttons</b>	Power, Action, volume up/down, 2 user-programmable
<b>Operating temperature</b>	14 to 122° F (-10 to 50° C)
<b>Storage temperature</b>	-40 to 178° F (-40 to 70° C)
<b>Relative humidity</b>	10% to 95% (noncondensing)
<b>Interfaces</b>	USB-C, 3.5 mm audio, NFC (ISO 14443, Tag Types 1-5)

Hardware Feature	Cisco Wireless Phone 840 (CP-840)
<b>Sensors</b>	<ul style="list-style-type: none"> <li>• Accelerometer</li> <li>• Gyroscope</li> <li>• Magnetometer (compass)</li> <li>• ALS/proximity</li> </ul>
<b>Durability</b>	<p>Ingress Protection Standard IP65 – protects against dust ingress</p> <p>Water-resistant – resists water splashed on device</p> <p>MIL-STD-810G drop testing – survives multiple 1.8 meter drops onto a steel plate</p>

Table 4 shows the software features for the Cisco Wireless Phone 800 Series.

**Table 4.** Software Features

Software Feature	Details
<b>Calling Features</b>	<ul style="list-style-type: none"> <li>+Dialing</li> <li>Adjustable ringing and volume levels</li> <li>Adjustable display brightness and timeout</li> <li>Audible and vibrating ringers</li> <li>Auto Answer</li> <li>Automatic keypad lock</li> <li>Auto-detection of headset and auto-answer from headset (BT)</li> <li>Call forward</li> <li>Call forward notification</li> <li>Callback</li> <li>Call history lists</li> <li>Call park</li> <li>Call Recording (CUCM)</li> <li>Call reject</li> <li>Call timer</li> <li>Call waiting</li> <li>Caller ID</li> <li>Corporate directory</li> <li>Conference</li> <li>Do Not Disturb (DND)</li> <li>Extension Mobility</li> <li>Extension Mobility Cross Cluster</li> <li>Failover, Fallback, Redundancy, Resiliency</li> <li>Forced authorization and client matter codes</li> <li>G.711u, G.711a, G.722, G.729a, and OPUS Codecs</li> </ul>

Software Feature	Details
	<p>Hold/Resume</p> <p>Hunt group login/logout</p> <p>Hotelling - login/logout (Webex Calling)</p> <p>Immediate divert</p> <p>Location Awareness and Reporting</p> <p>Merge</p> <p>Multiple Lines</p> <p>Music On Hold (MoH, non-multicast)</p> <p>Message Waiting Indication (MWI)</p> <p>Mute</p> <p>Redial</p> <p>Network profile support via EMM/MDM</p> <p>Shared Lines</p> <p>Support for Mutual-auth TLS</p> <p>Configuration Management (EMM Alternative)</p> <p>Synchronization of Contacts Through CUCM</p> <p>Iterative contact search</p> <p>Network Hold</p> <p>Noise Cancellation</p> <p>Pre-dialing before sending</p> <p>Personal directory</p> <p>Time and date display</p> <p>Phone app Reset and Restart through CUCM</p> <p>SIP Digest Authentication</p> <p>SIP Using TCP</p> <p>Speed Dial (on-phone configuration)</p> <p>Transfer: Announced, Blind</p> <p>Visual Voicemail</p>
<b>Codecs</b>	<ul style="list-style-type: none"> <li>• Opus</li> <li>• G.711a, G.711u</li> <li>• G.722</li> <li>• G.729a</li> </ul>
<b>Protocol</b>	Session Initiation Protocol (SIP)

Software Feature	Details
<b>Call Control</b>	Cisco Unified Communications Manager 11.5(1)SU8, 12.5(1)SU3, 14.0(1) Webex Calling with version 1.6 firmware or later
<b>Security Features</b>	WPA2-Personal, WPA2-Enterprise with 802.1X (EAP-TLS, PEAP and EAP-TTLS) with Opportunistic Key Caching (OKC), Cisco Client Key Management (CCKM) and 802.11r (Fast Transition) Secure Real-Time Transport Protocol, PCI Compliance
<b>Configuration Options</b>	<ul style="list-style-type: none"> <li>• Manual or Dynamic Host Configuration Protocol (DHCP)</li> <li>• Support for online firmware upgrades using Trivial File Transfer Protocol (TFTP)</li> <li>• Domain Name Service (DNS)</li> <li>• Simple Network Time Protocol (SNTP)</li> <li>• Lightweight Directory Access Protocol (LDAP)</li> <li>• XML and XHTML</li> </ul>
<b>Application Platform</b>	<ul style="list-style-type: none"> <li>• CP-840/CP-840S: Android OS 10</li> <li>• CP-860/CP-860S: Android OS 13</li> </ul>
<b>Barcode</b>	Barcode scanner and configuration application for devices configured with barcode scanner hardware (840S and 860S)
<b>Battery Life</b>	Provides details including current charge level, health and number of charge cycles completed
<b>Buttons</b>	Hardware button action customization
<b>Call Quality</b>	Provides Wi-Fi access metrics and preference options
<b>Cisco Phone</b>	Native dialer application that registers to Cisco Unified Communications Manager for calling purposes
<b>Custom Settings</b>	Device customization options that can be configured by a user or administrator
<b>Emergency</b>	Configuration and calling for emergency situations
<b>Logging</b>	Management of diagnostic information by the system administrator
<b>Push-To-Talk (PTT)</b>	Provides PTT radio multicast communication when configured via the appropriate multicast address for broadcast traffic
<b>System Updater</b>	Enables phone firmware updates
<b>Web API</b>	Application developer interface for external services and integration with XML applications
<b>User Localization</b>	Danish, Dutch, English (UK), English (US), Finnish, French (Canada), French (France), German, Hungarian, Italian, Norwegian, Portuguese (Brazilian), Spanish (Spain), Spanish (Columbia), Portuguese (Portugal), Slovenian, Russian, Swedish

Software Feature	Details
<b>Geographic Availability</b>	Albania Australia Austria Brazil Belgium Bosnia and Herzegovina Botswana Bulgaria Canada Cyprus Czech Republic Denmark Egypt Estonia Finland France Germany Gibraltar Greece Greenland Hong Kong Hungary Iceland Ireland Italy Japan Latvia Liechtenstein Lithuania Luxembourg Malta Mexico Monaco Montenegro Netherlands New Zealand North Macedonia

Software Feature	Details
	Norway
	Oman
	Poland
	Portugal
	Qatar
	Romania
	Saudi Arabia
	Singapore
	Slovakia
	Slovenia
	Spain
	Sweden
	Switzerland
	United Arab Emirates
	United Kingdom
	United States

## Wireless Features

The Cisco Wireless Phones support a multitude of wireless features including frequencies, channels and IEEE protocols. The details of wireless support are documented in the [deployment guide](#).

## Compliance Details

Table 5 shows the compliance details for the Cisco Wireless Phone 800 Series.

**Table 5.** Compliance Details

Category	Details
<b>Compliance Markings</b>	CE Markings per directives 2014/30/EU and 2014/35/EU and 2014/53/EU
<b>Safety</b>	ANSI/UL 62368-1-2019 CAN/CSA C22.2 No. 62368-1:19 EN 62368-1:2014, EN 62368-1:2014/AC:2015 EN 62368-1: 2014 +A11: 2017 IEC 62368-1:2014 AS/NZS 62368.1:2018 IEC 60529 (IP 54)

Category	Details
<b>Electromagnetic Compatibility and Electromagnetic Interference (EMC/EMI)</b>	47 CFR Part 15 Class B ICES-003 Class B EN 55035:2017 AS/NZS CISPR 35:2016 CISPR 35:2016 VCCI Class B EN 61000-3-2:2006, EN 61000-3-2:2006/A1:2009, EN 61000-3-2:2006/A2:2009 EN 61000-3-2:2014 EN 61000-3-3:2008 EN 61000-3-3:2013 EN 55035:2017 EN 61000-6-1:2007 EN 61000-6-3:2007, EN 61000-6-3:2007/A1:2011/AC:2012, EN 61000-6-3:2007/A1:2011 EN 300 386 V1.6.1 IEC 60601-1-2
<b>Telecom</b>	FCC Part 68 (CFR) (HAC) NZ PTC 220 DR AS/ACIF S004 and AS/ACIF S040 (Australia) TIA 810-B and TIA 920-A Canada-CS-03-HAC
<b>Radio</b>	Maximum EIRP for Mexico: <ul style="list-style-type: none"> <li>• CP-840/CP-840S:               <ul style="list-style-type: none"> <li>◦ 2.4G: 19.09 dBm</li> <li>◦ 5G: 16.94 dBm</li> </ul> </li> <li>• CP-860/CP-860S:               <ul style="list-style-type: none"> <li>◦ 2.4G: 18.96 dBm</li> <li>◦ 5G: 19.02 dBm</li> </ul> </li> </ul> USA: FCC Part 15.247 (2.4 GHz), FCC Part 15.407 (5 GHz), and FCC Part 2 Canada: RSS-210 Japan: ARIB STD-T66 (2.4 GHz), ARIB STD-T70, and T71 (4.9/5 GHz) ETSI: <ul style="list-style-type: none"> <li>• EN 300 328 v2.2.2;</li> <li>• EN 301 893 v2.1.1</li> </ul>

Category	Details
	<ul style="list-style-type: none"> <li>• EN 300 330 v2.1.1;</li> <li>• EN 300 440 v2.2.1</li> </ul> AS/NZS 4268:2017 A1 Singapore: IMDA TS SRD Hong Kong: HKTA1039
<b>RF Exposure</b>	OET-65C (01-01) ANSI C95.1 (91) RSS-102 ACA Radio Communications (Electromagnetic Radiation – Human Exposure) Standard 2003 EN 50360:2017 ETSI: EN 301 489-1 <ul style="list-style-type: none"> <li>• EN 301 489-3</li> <li>• EN 301 489-17</li> </ul>

## Ordering information

Cisco Wireless Phones and accessories can be ordered through certified Cisco partners. For more information about ordering and product configuration, partners can visit [the Cisco Ordering Home Page](#) or visit [the Partner Phone Ordering Guide](#).

The Cisco Wireless Phone 840 and 840S is sold as a phone and battery only, or as a phone, battery and charger bundle.

Table 6 shows the power options for the Cisco Wireless Phone 840 and 840S.

**Table 6.** Cisco Wireless Phone 840 power options

Category	Details
<b>Power</b>	<p>The 840 is a mobile device that requires a charged battery in order to operate. The phone can be charged with the USB-C charger and cable that are supplied with the bundle or with one of the stand-alone desktop chargers. Both the USB-C charger and the desktop chargers can be ordered individually.</p> <p>The single-unit phone and battery desktop chargers are sold without a power supply. Partners should order a desktop charger and a corresponding power supply for the appropriate region. The multi-charger ships with a charger.</p> <p>Example: To charge a single phone in a desktop charger, order the CP-840-PH-DCHR= and one of the following power supplies:</p> <ul style="list-style-type: none"> <li>• CP-840-DCHR-PS-AU=</li> <li>• CP-840-DCHR-PS-EU=</li> <li>• CP-840-DCHR-PS-NA=</li> </ul>

The Cisco Wireless Phone 860 and 860S is sold as a phone and battery only, or as a phone, battery and charger bundle.

Table 7 shows the power options for the Cisco Wireless Phone 860 and 860S.

**Table 7.** Cisco Wireless Phone 860 power options

Category	Details
Power	<p>The 860 is a mobile device that requires a charged battery in order to operate. The phone can be charged with the USB-C charger and cable that are supplied with the bundle or with one of the stand-alone desktop chargers. Both the USB-C charger and the desktop chargers can be ordered individually.</p> <p>The single-unit phone and battery desktop chargers are sold without a power supply. Partners should order a desktop charger and a corresponding power supply. The multi-charger base and bundles ship with a wall power cord to connect the base to wall power and does not require a separate power supply.</p> <p><b>Example:</b> To charge a phone or battery in a stand-alone desktop charger, order the CP-860-DCHR= and the CP-860-DCHR-PSU=.</p> <p>The multi-charger can be purchased as a bundle to charge 4 batteries and 4 phones, or in a separate configuration to charge 8 batteries. Additionally, the multi-charger base and desktop charger units can be purchased individually to create a purpose-built configuration.</p> <p><b>Example:</b> To charge 3 phones and 5 batteries in a multi-charger, order one(1) CP-860-MCHR=, three(3) CP-860-DCHR= and one(1) CP-860-BAT-DCHR=.</p>

Table 8 shows the part number ordering information for the Cisco Wireless Phone 800 Series.

**Table 8.** Ordering information

Part #	Product description
CP-800-USBCH=	Cisco 800 USB Cable with Worldwide Wall Charger
CP-840-BAT-MCHR=	Cisco 840 Multi-Charger for 6 Batteries with PSU
CP-840-BAT=	Cisco 840 Spare Battery
CP-840-BUN-K9	Cisco 840 Worldwide Phone, Battery, Cable, Charger
CP-840-CLIP=	Cisco 840 Non-Scanner Rotating Belt Clip Holster
CP-840-DCHR-PS-AU=	Cisco 840 Desktop Charger AU Power Supply
CP-840-DCHR-PS-EU=	Cisco 840 Desktop Charger EU Power Supply
CP-840-DCHR-PS-NA=	Cisco 840 Desktop Charger NA Power Supply
CP-840-DUAL-DCHR=	Cisco 840 Desktop Charger for 1 Phone and 1 Battery
CP-840-K9=	Cisco 840 Worldwide Phone and Battery Only
CP-840-PH-DCHR=	Cisco 840 Desktop Charger for 1 Phone

Part #	Product description
<b>CP-840-PH-MCHR=</b>	Cisco 840 Multi-Charger for 6 Phones with PSU
<b>CP-840S-BUN-K9</b>	Cisco 840S Worldwide Phone with Scanner, Battery, Cable, Charger
<b>CP-840S-CLIP=</b>	Cisco 840S Scanner Rotating Belt Clip Holster
<b>CP-840S-HANDLE=</b>	Cisco 840S Scanner Handle
<b>CP-840S-K9=</b>	Cisco 840S Worldwide Phone with Scanner and Battery Only
<b>CP-860-BAT-DCHR=</b>	Cisco 860 Desktop Charger for Dual Batteries Only
<b>CP-860-BAT-MCHR-BN</b>	Cisco 860 Multi-Charger Bundle for 8 Batteries
<b>CP-860-BAT=</b>	Cisco 860 Spare Battery
<b>CP-860-BUN-K9</b>	Cisco 860 Worldwide Phone, Battery, Cable, Charger
<b>CP-860-CASE=</b>	Cisco 860 Non-Scanner Case with Clip
<b>CP-860-CLIP=</b>	Cisco 860 Non-Scanner Clip
<b>CP-860-DCHR-PSU=</b>	Cisco 860 Desktop Charger WW Power Supply
<b>CP-860-DCHR=</b>	Cisco 860 Desktop Charger for Phone and Spare Battery
<b>CP-860-K9=</b>	Cisco 860 Worldwide Phone and Battery Only
<b>CP-860-MCHR-BN</b>	Cisco 860 Multi-Charger Bundle for 4 Phones and 4 Batteries
<b>CP-860-MCHR=</b>	Cisco 860 Multi-Charger Base with Power Supply
<b>CP-860S-BUN-K9</b>	Cisco 860S Worldwide Phone with Scanner, Battery, Cable, Charger
<b>CP-860S-CASE=</b>	Cisco 860 Scanner Case with Clip
<b>CP-860S-CLIP=</b>	Cisco 860 Scanner Clip
<b>CP-860S-K9=</b>	Cisco 860S Worldwide Phone with Scanner and Battery Only
<b>SP-CP-860-EX-CARE=</b>	Extended hardware replacement coverage for Cisco 860, only available in North America (US & CA)
<b>SP-CP-860S-EXCARE=</b>	Extended hardware replacement coverage for Cisco 860S, only available in North America (US & CA)

---

## Warranty information

Cisco Wireless Phones are covered by a Cisco standard 1-year replacement warranty. A Cisco Smart Net Total Care® optional service agreement is available for the Cisco Wireless Phone 840. The Cisco Wireless Phone 860 cannot be covered by a Smart Net Total Care agreement. Cisco Wireless Phone batteries and other accessories are covered by Cisco's limited 90-day warranty. Approved warranty replacement for the Cisco Wireless Phone 860 will be provided via new product order fulfillment within current product order lead-time.

## Cisco environmental sustainability

Information about Cisco's environmental sustainability policies and initiatives for our products, solutions, operations, and extended operations or supply chain is provided in the "Environment Sustainability" section of Cisco's [Corporate Social Responsibility](#) (CSR) Report.

Reference links to information about key environmental sustainability topics (mentioned in the "Environment Sustainability" section of the CSR Report) are provided in the following table:

Sustainability topic	Reference
Information on product material content laws and regulations	<a href="#">Materials</a>
Information on electronic waste laws and regulations, including products, batteries, and packaging	<a href="#">WEEE compliance</a>

Cisco makes the packaging data available for informational purposes only. It may not reflect the most current legal developments, and Cisco does not represent, warrant, or guarantee that it is complete, accurate, or up to date. This information is subject to change without notice.

## Cisco Capital

### Flexible payment solutions to help you achieve your objectives

Cisco Capital makes it easier to get the right technology to achieve your objectives, enable business transformation and help you stay competitive. We can help you reduce the total cost of ownership, conserve capital, and accelerate growth. In more than 100 countries, our flexible payment solutions can help you acquire hardware, software, services and complementary third-party equipment in easy, predictable payments. [Learn more](#).

---

## Document history

This document is periodically updated to reflect the current supported capabilities of the Cisco Wireless Phone 800 Series. This document was last updated on November 17, 2022.

**Americas Headquarters**  
Cisco Systems, Inc.  
San Jose, CA

**Asia Pacific Headquarters**  
Cisco Systems (USA) Pte. Ltd.  
Singapore

**Europe Headquarters**  
Cisco Systems International BV Amsterdam,  
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at <https://www.cisco.com/go/offices>.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: <https://www.cisco.com/go/trademarks>. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)